



CE-PTZ26x

Specifications

| Camera | CE-PTZ26x |
|---------------------------------|--|
| Image Sensor | 1/4 Inch SONY Ex-View CCD |
| Resolution | 470 / 540 TV Lines (High Resolution Mode) |
| Effective Pixels | Approx. 440,000 Pixels |
| Sync System | Internal / External (V-Lock) |
| Scanning System | Progressive |
| S/N Ratio | More than 50dB |
| Minimum Illumination | Day: 2.0 Lux (1/50), 0.14 Lux (1/4) Night: 0.7 Lux (1/50), 0.05 Lux (1/4) |
| Shutter Speed | 1/1 ~ 1/10,000 sec. |
| Lens | 3.5 ~ 91mm (26x Optical Zoom, F1.6 to F3.8) |
| Digital Zoom | 12x (120x with Optical Zoom) |
| White Balance | Auto / Manual / Wide Dynamic Range |
| Gain Control | Auto / Manual (-3 to 28dB, 2dB Steps) |
| AE Control | Auto, Manual, Priority Mode, Bright, Slow AE, EV Compensation, Back Light Compensation |
| Back Light Compensation | On / Off |
| Privacy Zone Masking | On / Off (24 Positions) |
| Picture Effects | E-Flip, Nega Art, Black & White, Mirror Image |
| Video Output | 1.0 Vp-p, 75Ω |
| Functions | |
| Presets | 128 Preset Positions |
| Tours | 16 Preset Tour Sequences with 32 Presets each |
| Patterns | 4 Self-Learning Pattern Sequences |
| Scans | 1 Scan Sequence |
| On Screen Display (OSD) | OSD for Configuration Setup |
| Interface | RS-485, Multiple protocols |
| Protocols | CLINTON, ALEC, PELCO-P9600, PELCO-P4800, PELCO-D2400, A 01, SANTACHI 650, SANTACHI 450, PEARMAIN, KONY 19.2KB, KONY 20.832, HD 600, LILIN, KALATEL, VCL, TOTA, WJ-FS616, PHILIPS, AD (Consult PTZ manual for Dip Switch settings) |
| Buadrate (RS485 / RS422) | 2400/4800/9600/19200bps Soft Select |
| Temperature Indicator | Intelligent Thermal-Control |
| Idle Protection | User Definable Action |
| Construction | |
| Case Construction | Aluminum-Alloy Housing |
| Mechanisms | High Precision Aluminum Construction |
| Operation | Designed for 24/7 Operation |
| Pan Rotation Range | 360° Continuous |
| Tilt View Range | 0 - 90° with Auto-Flip |
| Pan Speed | 0.4° - 320°/sec |
| Tilt Speed | 0.4° - 150°/sec |
| Unit as a Whole | |
| Power Consumption | 2 Amps (AC24V) |
| Power Requirement | AC24V |
| Operating Temperature | -4° F ~ 140° F |
| Weather Rating | IP66 |

Information in this document is subject to change

Features

- 540 TVL SONY Ex-View
- Aluminum Alloy Construction
- Intelligent Temperature Control
- IP66
- Includes 1 Spare Dome Cover
- Multiple Protocols Supported
- Low-noise, High Speed
- OSD Configuration Menu
- Path Memory Function
- Privacy Masking
- 128 Presets
- 3.5 ~ 91mm Lens
- 26x Optical Zoom
- 12x Digital Zoom
- 0.4 - 300°/sec. Pan Speed
- -0.4 - 150°/sec. Tilt Speed
- 360° Horizontal
- 0 - 90° Vertical
- RS 485 Communication
- AC24V Input