

CE-S320-B

DC24V (12.5 Amp) 3 PVM Power Supply



KEY FEATURES:

- DC24V, 12.5 Amps
- 320 Watt Output
- 3 Pigtail (+/-) DC24V Outputs
- Adjustable Voltage from DC 20-27V
- Short Circuit, Overload, Over Voltage, and Temperature Protection
- Truss Mount, 19" Rack Mount, & Wall Mount
- Recommended for all Clinton DC24V LCDs or PVMs
- UL Listed

POWER

Input Voltage	88 - 132VAC / 176 - 264VAC (selectable by switch)
Output Voltage	20-27 VDC
Total Outputs	3 Ch (+/- pigtail with butt-splice connectors)
Total Amps	12.5 Amps
DC Adjustment Range	+/-10% rated output voltage
Overload Protection	105% - 135% rated hiccup mode, auto-recovery
Over Voltage Protection	115% - 145% rated output voltage
Setup, Rise, Hold Up Time	3000ms, 50ms, 8ms @ full load & 110VAC
Withstand Voltage	I/P-O/P:3KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC

GENERAL

Materials	Steel Enclosure
Certifications	UL Listed, FCC, CE
Operating Temperature	32°F - 104°F / 0°C - 40°C
Dimensions	19" (W) x 5" (D) x 3.5" (H) 484.6mm (L) x 127mm (W) x 88.9mm (H)
Weight	9.4 lbs / 4.26 kgs

ASSEMBLY:

