## clintonelectronics

## **CE-PS200**

DC24V (5 Amp) 1ch PVM Power Supply



<b>KEY</b>	<b>FEAT</b>	URES:
------------	-------------	-------

- · DC24V 5.0 Amps, 120W Output
- · 2.1mm barrel plug
- · Includes Female Pigtail (+/-) for Long Runs
- · Includes Mounting Bracket
- $\cdot$  Recommended for all Clinton DC24V LCDs or PVMs
- · UL Listed

INPUT	
Input Voltage	100-240VAC
Input Current	≤2A
Inrush Current	120A/230VAC
Hold Up Time	≥8.3ms
Turn On Time	<b>≤</b> 3s

OUTPUT	
Over Voltage Protection	Latch-off
Short Circuit Protection	Auto Recovery
Max Output	120W
Output Voltage	24VDC
Max Load	5A

GENERAL		
Total Outputs	1 Ch (2.1mm male barrel plug, includes female pigtail adapter)	
Certifications	UL Listed (C/US), FCC, CE, TÜV SÜD, EAC	
Operating Temperature	14°F ~ 100°F / -10°C ~ 37.77°C	
Dimensions	5.39" (L) x 2.36" (W) x 1.38" (H) 137mm (L) x 60mm (W) x 35mm (H)	
Weight	0.85 lbs / 0.38 kg	

## **DIMENSIONS:** (Mounting Bracket Removed)

