

CE-M32FA51-B


32" PVM w/ AXIS IP Camera - Black



KEY FEATURES:

- Built-In AXIS® FA51 Camera Unit w/ FA1105 Sensor Unit
- 1920 x 1080 Resolution / 16:9 Aspect Ratio
- 400 nit Brightness / 4,000:1 Contrast Ratio
- Steel Cabinet
- Motion detection triggers flashing LED lights and/or on-screen banner overlay message (*Recording In Progress, Monitoring In Progress, etc...*)
- 2 RGB LED light strips, selectable colors & flash rate
- 1 RJ45 Ethernet Port
- 1 Alarm Input (+/-): triggers "Please Return to Cashier" message
- VESA 100 (M4)
- PoE++ or DC24V (Power Supply Sold Separately)
- TÜV SÜD Compliant, NDAA & TAA Compliant

DIMENSIONS:



MONITOR

Display	32" LED Backlight LCD
Resolution	1920 x 1080
Aspect Ratio	16:9
Display Colors	16.7M (8 BIT)
Brightness	400 nit
Contrast Ratio	4000:1
Viewing Angle (H x V)	178° x 178°
Response Time	6.5ms

CAMERA

Image Sensor	1/3" Progressive Scan RGB CMOS
Lens	2.8mm (F2.0) Lens
Field of View	111° (Horizontal) / 61° (Vertical)
Minimum Illumination	0.2 Lux (Color)
Shutter Speed	1/32500 - 1/30 sec.

VIDEO

Video Compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG
Resolution	1920x1080 (1080p) to 160x90
Frame Rate	Up to 30 fps
Video Streaming	Multiple, individually configurable streams in H.264 and Motion JPEG, Axis Zipstream technology in H.264, Controllable frame rate and bandwidth

NETWORK

Security	IP address filtering, HTTPS encryption, IEEE 802.1x (EAP-TLS) network access control, multi-level user, signed video, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified)
Network Protocols	IPv4, IPv6, USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, RTCP, DHCP, SSH, CDP, MQTT, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

SYSTEM

Event Actions	Toggle I/O, send images, publish MQTT, send notifications, overlay text, recordings, SNMP trap messages, status LED, video clips MQTT publish
Event Triggers	Device status, edge storage, I/O, PTZ, scheduled event, video MQTT subscribe

GENERAL

Mounting	VESA 100 (M4)
Connectors	1 RJ45 Network Output Alarm Input (+/-)
Power Requirement	PoE++ (IEEE 802.3bt) or 24VDC
Power Consumption (±10%)	PoE++: 58 Watts / DC24V: 48 Watts (2 Amps)
Operating Temperature	32°F - 122°F / 0°C - 50°C
Dimensions (W x H x D)	28.5" x 18.375" x 2.125" 72.4cm x 46.67cm x 5.39cm
Weight	22.2 lbs / 10.06 kgs

RECOMMENDED POWER SUPPLY

CE-PS195	Single Port PoE++ (95W) Injector
CE-PS400POE	Four Port PoE++ (90W/port - 360W total) Injector
CE-PS200	DC24V (5A/120W) Single PVM Power Supply
CE-S320-B	DC24V (12.5A/320W) 3 PVM Power Supply
CE-S600-24-B	DC24V (25A/600W) 3 PVM Power Supply

CERTIFICATIONS:

