clintonelectronics



CE-P43E-B


43" EX-SDI Connect PVM (Black)



KEY FEATURES:

- · 43" Portrait Mode Digital Signage PVM
- \cdot 16:9 Aspect Ratio / 1920 x 1080 Resolution
- $\cdot\,$ 500 nit Brightness / 4000:1 Contrast Ratio
- Screen content and scheduling is easily customized with included cloudbased Clinton Connect software
- · Ads are updated via networked connection (Wifi or Ethernet)
- · Built-In 2MP Clinton IP Camera
- · 2.7~13.5mm (f1.4) Motorized True D/N Auto Focus Zoom Lens
- · Built-in WiFi
- \cdot Built-In front facing speakers & Bluetooth
- · Steel Beze
- \cdot Programable LED Lightbars and flashing LEDs
- · Video, Power & Network connections are secured behind cover plate
- \cdot 1 RJ45 Network Connection, 1 RJ45 IP Camera Connection
- · 2 Alarm Inputs (terminal block)
- · VESA 200x200, 200x400 (M6)
- · Dual Voltage: AC110-240V or DC24V (power supply sold separately)
- · UL Listed, NDAA & TAA Compliant

DIMENSIONS:



| MONITOR | |
|-----------------------|--------------------------------|
| Display | 43" WLED Backlight LCD (AMVA3) |
| Resolution | 1920 x 1080 |
| Aspect Ratio | 16:9 |
| Display Colors | 16.7M (8 BIT) |
| Brightness | 500 nit |
| Contrast Ratio | 4000:1 |
| Viewing Angle (H x V) | 178° x 178° |
| Response Time | 8ms |

| CAMERA | |
|----------------------|---|
| Image Sensor | 1/2.8" SONY Starvis 2.1 Megapixel CMOS Image Sensor |
| Lens | 2.7-13.5mm (f1.4) Motorized True D/N Auto Focus Zoom Lens |
| Field of View | 106.1° (Horizontal) / 55.2° (Vertical) |
| Minimum Illumination | 0.2 Lux (Color) / 0.04 Lux (B&W) |
| Shutter Speed | 1/4 ~ 1/10,000 sec. |

| GENERAL | |
|------------------------|---|
| Alarm Input | 1 Terminal Block Alarm Input (Alarm 1 / Alarm 2) |
| Network | 1 RJ45 Ethernet Port - Camera Connection Only 1 RJ45 Ethernet Port - Clinton Connect Media Download Built-In Wifi (2.4GHz) - Clinton Connect Media Download |
| Mounting | VESA 200x200, 200x400 (M6) |
| Material | Steel Bezel |
| Power Consumption | 2.75A / 70 Watts (DC24V) |
| Power Requirement | DC24V or 110VAC |
| Operating Temperature | 32°F ~ 104°F / 0°C ~ 40°C |
| Dimensions (W x H x D) | 22.375" x 40" x 3" / 568.325mm x 1016mm x 76mm |
| Weight | 37.6 lbs / 17.05 kgs |

| CLINTON CONNECT - Software | |
|----------------------------|--|
| Supported Web Browsers | Chrome, Safari, Edge |
| Advertising Components | Text Ticker, Images, Video, Camera Feed, Slideshow |
| Image Format | JPG, PNG, BMP |
| Video Format | MP4, MOV, AVI |
| Media Storage | 100 GB Total— Monthly upload limits |

| RECOMMENDED POWER SUPPLY | |
|--------------------------|--|
| CE-PS200 | 120W Single Monitor Power Supply (24VDC) |
| CE-S320-B | 320W Multiple Monitor Power Supply (24VDC) |
| CE-600-24-B | 600W Multiple Monitor Power Supply (24VDC) |

SPECIAL ORDER ITEM

Low-stock Item. Inquire for lead time before ordering.

CERTIFICATIONS:







