

CE-CPPMD

Camera Pole Pendant Mount Dome Housing



GENERAL

Materials	Polycarbonate
Dimensions (Dia. x H)	7.28" x 8.12" / 185mm x 206.25mm
Weight	1.0 lbs / 0.45 kgs

COMPATIBLE CLINTON CAMERAS POLE MOUNTING PLATES & ADAPTERS

CE-CPUPR	Universal Round Mounting Plate, 4.45" Dia.
CE-CPFM	Universal Pendant Mount, Adjustable from 3" - 5.25" Dia.
CE-CPUPM	Universal Pendant Mount, 5" Dia.
CE-CPPA	3/4" EMT to 1-1/2" NPT Female Adapter
CE-CPPA-P	3/4" EMT to 1-1/2" NPT Female Adapter, Plastic
CE-CPPA-NPS	3/4" EMT to 1-1/2" NPS Female Adapter
CE-CPMPA	3/4" EMT to 1-1/2" NPS Male Adapter
CE-CPCA-W	3/4" EMT Threaded Conduit Adapter
CE-CP3105	Pendant Mount Adapter for Axis FA3105-L Camera
CE-CP-U	U-Bracket for Telescoping Camera Poles (M8-1.25)
CE-CP-U-1420	U-Bracket for Telescoping Camera Poles (1/4"-20)


KEY FEATURES:

- Clean, professional dome housing for pendant-mounted security cameras
- Universal design supports camera housings up to 6" in diameter
- Compatible with all Clinton CP Series Telescoping Poles
- Supports a wide range of camera types, including micro domes, vandal domes, fisheye, and turret cameras
- Adjustable height via top cap positioning for flexible installation
- Includes two camera masks: cutout mask for use with installed cameras & full mask for dummy dome applications
- Easy dome installation with snap-fit design
- Lightweight, durable polycarbonate construction

REQUIREMENTS:

- CP Series Camera Pole (sold separately)
- CP Series Universal Pendant Mount (sold separately)


MASK OPTIONS:



No Mask
IR & 360° Cameras



Cutout Mask
Non-IR Cameras



Full Mask
Dummy Dome

DIMENSIONS:

